## **MODULE PART NUMBERING SYSTEM**

Module AGM = AZ Displays Graphic Module ACM = AZ Displays Character Module Туре

1602 = 16x22464 = 240x64Module Format 2004 = 20X4 $3224 = 320 \times 240$ 4002 = 40x2 $1264 = 128 \times 64$ 

Design A through ZZ for different PCB sizes controller IC's, etc. (Combine with module format to Version arrive at base model number.)

R = Reflective F = Transflective Polarizer Type M = Transmissive, Positive N = Transmissive, Negative

Backlight Type N = NoncE = ELL = Yellow LED C = CCFTLW = White LED

T = TNG = Gray mode STN Fluid 6 B ≈ Blue mode STN Type F = FSTN (Film-compensated STN [B/W]) Y = Yellow mode STN

Viewing B = Bottom View (6 o'clock) L = Left View (9 o'clock)7 T = Top View (12 o'clock)Direction R = Right View (3 o'clock)

Temperature S = Standard temp range requiring single supply voltage Range D = Standard temp range requiring dual supply voltages 8 W = Wide temp range requiring single supply voltage And

Power Supply If = Wide temp range requiring dual supply voltages

T = Touch Screen 9

> ACM 1602M -6 7 8

= Character Module 6 = Yellow Mode STN 2 + 3 = Base Model Number 7 = Bottom View

= Reflective Polarizer 8 = Standard Temp Range with Single Supply Voltage

= No Backlight 9 = Options

**Options**